

# Self Learning Remote Controls\Electronic Override Keys For GR480

## Remote Controls

This system can be programmed with up to a maximum of 4 Remotes and 4 Electronic Override Keys at any one time. All Remotes required to operate this system must be present and programmed at the same time. Enter the Self Learning mode by: A) Open the door to which the Yellow wire is connected and leave it open. B) Turn the ignition to 'ON'. Do not start the engine. C) Momentarily touch one of the Electronic override keys onto the dashboard LED/Reader. **The siren will give 3 audible tones to indicate entry into the Self Learning mode.**

## Programming Remotes

D) Pick up one of the remotes and press both buttons simultaneously until the LED of the remote goes out. (approximately 10 seconds). Release both buttons and the LED will come on constantly.

- E) Depending on the type of remote press either the red or the ribbed button once. This will be acknowledged by:
- F) - a single flash of the dashboard LED/Reader.
- G) - a single tone of the siren.

### **This remote has now been programmed**

Repeat steps D & E to code the remaining remotes. When all the remotes have been programmed, turn the ignition to 'OFF'. This will be acknowledged by 3 siren tones. Test each Remote to ensure correct operation.

**Electronic Override Keys** All Override keys, including at least one of the *originals*, required to operate this system must be present and programmed at the same time. Enter the Self Learning mode by: A) Open the door to which the Yellow wire is connected and leave it open. B) Turn the ignition to the 'ON' position. Do not start the engine. C) Momentarily touch one of the Electronic override keys onto the dashboard LED/Reader. **The siren will give 3 audible tones to indicate entry into the Self Learning mode**

- D) First touch one of the *Original* Override keys onto the dashboard LED/Reader. This will be acknowledged by:
- E) - a single flash of the LED
- F) - a single tone of the siren.

### **This Override key has now been programmed**

Repeat step (D) for ALL the remaining Override Keys including the one that was used in step (C).

Once all the Electronic Override Keys have been programmed, turn the ignition 'OFF'. This will be signalled by 3 siren tones. Test each key to ensure correct operation. (Refer to User Instructions).

**NOTE: IT IS IMPORTANT TO KEEP THE ORIGINAL OVERRIDE KEYS ' IN A SAFE PLACE AS AT LEAST ONE OF THEM MUST ALWAYS BE USED IN THE PROGRAMMING PROCEDURE.**